

# Compressed Air Blow Guns



**Safety  
Controlled-  
Flow**

**OSHA  
Compliant**

## LEVER OPERATED HANDY-AIR™ BLOW GUN



CATALOG NO.

PRESSED SAFETY TIP	BG2L-30STP
THREADED SAFETY TIP	BG2L-30STT
PRESSED STANDARD TIP	BG2L-30P
THREADED STANDARD TIP	BG2L-30T

## BUTTON OPERATED HANDY-AIR™ BLOW GUN



CATALOG NO.

BG2-30STP
BG2-30STT
BG2-30P
BG2-30T

## NICKEL PLATED HANDY-AIR™ BLOW GUN



CATALOG NO.

BG2L-STT

Our bright nickel plated, Lever Operated Blow Guns offer the same quality features as the other Handy-Air™ Blow Guns at an economical price.

### INLET PRESSURE

- 150 PSIG maximum

### TEMPERATURE

- 32°-180° F

### FLOW

- Safety Tip: 19.8CFM@100 PSIG
- Standard Tip: 9.3 CFM@100 PSIG

### BODY

- Diecast Zinc

### SEAL

- Buna-N

### INLET

- 1/4" FPT

### SAFETY TIP - STANDARD TIP

Handy-Air models are available with either the standard or ST safety tip, each of which may be ordered pressed or threaded to the gun. The pressed tip is not removable and prevents tampering. The threaded tip has a 1/8" NPT male thread. The ST safety tip provides a conical shield of air which encircles blown chips or particles directing them away from the operator.



## Non-Regulated Blow Guns

Standard model blow guns are available for those installations not requiring reduced pressure. These two diecast models are not OSHA compliant.

Cat. No. BG2 (Button Operated)  
Cat. No. BG2L (Lever Operated)

**Safety  
Controlled-  
Flow**

**OSHA  
Compliant**

## PISTOL GRIP BLOW GUN



CATALOG NO.

PRESSED SAFETY TIP	PG2P
THREADED SAFETY TIP	PG2T

### INLET PRESSURE

- 150 PSIG

### TEMPERATURE

- 32° - 120° F

### FLOW

- 19.8 CFM @ 100 PSIG

### BODY

- Nylon 6

### SEAL

- Buna-N

### INLET

- 1/4" FPT

### FEATURES

- OSHA Compliant
- Pistol grip design is more comfortable to operate.
- Trigger/Valve design allows for variable output.
- Safety tip standard
- Trigger serves as a convenient hanging hook.
- Color, safety yellow.

## Blowgun Accessories



### #EX12 12" Extension

- Permanent extension.
- Employs same tip as gun.
- Dynamic and static pressures same as gun installed on.



### #EX10DH 10" Extension

- Removable extension, push on, twist off.
- Durable tubing with female tapered fitting.
- Fits snugly on standard or safety tip.



### #EX2RT Rubber Tip

- Protects delicate parts from damage
- Blowguns with rubber tip will not comply with OSHA requirements.
- Installs on all threaded blowguns with 1/8" NPT