



Three Way Sleeve Valves & Swivel Fittings

"FOST-AIR" THREE WAY SLEEVE VALVE



SLEEVE VALVE
CATALOG NO.

LOCKOUT
CATALOG NO.

1/8 NPT
1/4 NPT
3/8 NPT
1/2 NPT

3W125
3W250
3W375
3W500

LO250
LO375
LO500

FEATURES:

- Provides low cost ON-OFF-EXHAUST operation.
- Slide the sleeve to the ON position. Exhaust ports are closed, valve is open. Reversing the sleeve, opens exhaust ports, shuts off flow.
- Ports covered for protection against exhaust flow.

- Patented body detent secures sleeve position.
- Valve with lockout complies with OSHA Standard 29 CFR, Part 1910

WORKING PRESSURE:

- to 200 PSIG

TEMPERATURE:

- - 25° to +200°F

PERFORMANCE DATA

	Air Flow – CFM 10 PSIG Pressure Drop	
	100 PSIG	80 PSIG
1/8 NPT	16	14.5
1/4 NPT	40	36
3/8 NPT	65	59
1/2 NPT	140	127

Swivel

Free Swivel Under Pressure

90° SWIVEL



CAT. NO.

1/4 MPT X 1/4 FPT 25US90

MALE BARBED INSERT



CAT. NO.

1/4 MPT X 1/4 ID M7S
3/8 MPT X 3/8 ID M13S
1/2 MPT X 1/2 ID M17S

PUSH-ON SWIVEL



CAT. NO.

1/4 MPT X 1/4 ID PM7S
3/8 MPT X 3/8 ID PM13S
1/2 MPT X 1/2 ID PM17S

MALE TO FEMALE PIPE



CAT. NO.

1/4 MPT X 1/4 FPT 25US
3/8 MPT X 3/8 FPT 38US
1/2 MPT X 1/2 FPT 50US

360 Degree Universal Swivel, 1/4" NPT

360° SWIVEL



CAT. NO.

1/4 MPT X 1/4 FPT 25US36

BENEFITS

- Swivels 360 degrees in two independent planes
- Allows air hose to hang straight down when used with air tools
- Reduces operator fatigue
- Reduces the possibility of carpal tunnel syndrome
- Increases air hose life.

MAXIMUM WORKING PRESSURE

- 300 PSIG

MATERIALS OF CONSTRUCTION

- Body: Brass and plated steel
- Seals: Buna N

SPECIFICATIONS

- Pipe size: 1/4" NPT male x 1/4" NPT female